



Third West Air Monitor Result Shepherd, Michael to:

Joyce Ackerman, 'Craig Barnitz (cbamitz@utah.gov)'

11/09/2011 02:19 PM

Hide Details

From: "Shepherd, Michael" < Michael. Shepherd@PacifiCorp.com>

To: Joyce Ackerman/R8/USEPA/US@EPA, "'Craig Bamitz (cbamitz@utah.gov)'" <cbamitz@utah.gov>

1 Attachment



Joyce & Craig,

We had a positive hit on November 7, 2011. It was one fiber of chrysolite. See the attached. Please let me know if you have any questions or concerns.

Thanks,

Mike Shepherd
Project Manager
Rocky Mountain Power - Major Projects
801.220.4584 Office
801.631.1310 Cell
801.220.2797 Fax
michael.shepherd@pacificorp.com



November 9, 2011

Laboratory Code:

RES

Subcontract Number: Laboratory Report:

NA

Project # / P.O. #

RES 223858-1 None Given

Project Description:

3rd West Sub Station -

RMP

Eldon Romney R & R Environmental 47 West 9000 South #2 Sandy UT 84070

Dear Customer,

Reservoirs Environmental, Inc. is an analytical laboratory accredited for the analysis of Industrial Hygiene and Environmental matrices by the National Voluntary Laboratory Accreditation Program (NVLAP), Lab Code 101896-0 for Transmission Electron Microscopy (TEM) and Polarized Light Microscopy (PLM) analysis and the American Industrial Hygiene Association (AIHA), Lab ID 101533 - Accreditation Certificate #480 for Phase Contrast Microscopy (PCM) analysis. This laboratory is currently proficient in both Proficiency Testing and PAT programs respectively.

Reservoirs Environmental, Inc. has analyzed the following samples for asbestos content as per your request. The analysis has been completed in general accordance with the appropriate methodology as stated in the attached analysis table. The results have been submitted to your office.

RES 223858-1 is the job number assigned to this study. This report is considered highly confidential and the sole property of the customer. Reservoirs Environmental, Inc. will not discuss any part of this study with personnel other than those of the client. The results described in this report only apply to the samples analyzed. This report must not be used to claim endorsement of products or analytical results by NVLAP or any agency of the U.S. Government. This report shall not be reproduced except in full, without written approval from Reservoirs Environmental, Inc. Samples will be disposed of after sixty days unless longer storage is requested. If you have any questions about this report, please feel free to call 303-964-1986.

Sincerely,

Jeanne Spencer Orr

President

RESERVOIRS ENVIRONMENTAL, INC.

NVLAP Lab Code 101896-0; TDH: #30-0015

TABLE I. TEM AIR FILTER SAMPLE DATA AND ANALYTICAL RESULTS

RES Job Number:

RES 223858-1

Client:

R & R Environmental

Client Project Number / P.O.: None Given

Client Project Description:

3rd West Sub Station - RMP

Date Samples Received:

November 8, 2011

Analysis Type:

TEM, AHERA

Turnaround:

24 Hour

Date Samples Analyzed:

November 8, 2011

Client ID Number	Lab ID Number		Area Analyzed	Air Volume Sampled	Number of Asbestos Structures Detected	Analytical Sensitivity	Asbestos Concentration	Filter Loading	
			(mm²)	(L)		(s/cc)	(s/cc)	(s/mm²)	
3W110711-E	EM	8207 3 7	0.0770	1079	ND	0.0046	BAS	BAS	
3W110711-S	EM	8207 3 8	0.0770	1079	ND	0.0046	BAS	BAS	
3W110711-N	EM	8207 3 9	0.0770	1094	1	0.0046	0.0046	13 .0	
3W110711-W	EM	820740	0.0770	1094	ND	0.0046	BAS	BAS	

NA = Not Analyzed

ND = None Detected

BAS = Below Analytical Sensitivity

Average Grid Opening in mm² = 0.011

Filter Material = Mixed Cellulose Ester

Filter Diameter = 25 mm

Effective Filter Area = 385 sq mm

DATA QA

RESERVOIRS ENVIRONMENTAL, INC.

NVLAP Lab Code 101896-0; TDH: #30-0015

TABLE II. SUMMARY OF ANALYTICAL DATA

RES Job Number:

RES 223858-1

Ciient:

R & R Environmental

Client Project Number / P.O.: None Given

Client Project Description:

3rd West Sub Station - RMP

Date Samples Received:

November 8, 2011

Analysis Type:

TEM, AHERA

Turnaround:

24 Hour

Date Samples Analyzed:

November 8, 2011

Client ID Number	Lab ID Number		Asbestos Mineral	Asl	pestos Stri	ıcture Typ	es*	Structures >5 Microns in Length	**Excluded Structures	Asbestos Structures for	
			•	Fibers	Bundles	Clusters	Matrices			Concentration	
3W110711-E	ЕМ	820737	ND	0	0	0	0	0	0	0	
3W110711-S	EM	820738	ND	0	0	0	. 0	0	0	0	
3W110711-N	EM	8 2 07 3 9	Chrysotile	1	0	0	0	0	0	1	
3W110711-W	EM	820740	ND	0	0	0	0	0	0	0	

^{*}See Analytical Procedure for definitions

ND = None Detected

^{**}C = Excluded from total due to lack of confirmation

^{**}L = Excluded from total for length less than 0.5 micron (AHERA only)

^{**}A = Excluded from total due to incorrect aspect ratio

Reservoirs Environmental, Inc. 5601 Logan St. Cerwer, OO 60216 • Pij; 303 964-1966 • Fax 303-477-4278 • ToA Free : 966 RESI-ENV

Pager: 303-609-2098 **CONTACT INFORMATION:** INVOICE TO: (IF DIFFERENT) Contect Dave Roskelley Functionmental Phone: Fac Soudy Ut 84070 Cell/peger 801 541-1035 Final Data Daliveratrie Email Addresa: Project Number and/or P.O. #: Project DescriptionAccation: 3 22 West Substation - RNIP dave & Trenstrown **REQUESTED ANALYSIS** VALID MATRIX CODES LAB NOTES: ASBESTOS LABORATORY HOURS: Weekdays: 7am - 7pm PLM / PCM / TEM RUSH (Same Day) PRIOR/TY (Next Day) STANDARD Bulk = BAir = A(Rust: PCM = 2hr. TEM = 6hr.) Dust = DPaint = P CHEMISTRY LABORATORY HOURS: Weekdays: 8am - 5pm Soll = S Wipe ≃ W 1194 Metal(s) / Dust RUSH 24 hr. 3-5 Day Swab = SW F = Food **Prior notification la RCRA 8 / Metals & Welding Drinking Water ≈ DW Waste Water = WW Short report, Long report, Point Count RUSH 5 day 10 day required for RUSH Fume Scan / TCLP O = Other ₹ 5 turnarounds.** Organics 24 hr. 3 day 5 Day **ASTM E1792 approved wipe media only** MICROBIOLOGY LABORATORY HOURS: Weekdays: 9am - 6pm E.coll 0157:H7, Coliforms, 5, aureus 2 Day 3-5 Day Salmonella, Listeria, E.coli, APC, Y & M Mold RUSH 24 Hr 48 Hr ___ S Day "Tumaround times establish a laboratory priority, subject to laboratory volume and are not guaranteed. Additional faes apply for aftertiours, waskends and holidays.** Code Special Instructions: (L) / Area EM Number (Laboral Date Time Use Only) Co!lected Collected Client sample ID number (Sample ID's must be unique) MICRORIOLOGY mm/dd/yy hh/mm e/o nlozli 3W 110711 - F 3W 1W711 - S 13W 1W7U - N 3w 4074 - W 8 9 10 Number of samples received: (Additional samples shall be listed on attached long torm.) NOTE: REI will analyze incoming samples best upon frigonitation received and will not be responsible for errors or omissions in calculations resulting from the inaccuracy of original data. By signing dient/campany representative agrees that submission of the following samples for requested analysis as indicated co this Onain of Custody shall constitute en analytical services agreement with payment terms of NET 30 days, failure to comply with payment terms may result in a 1.5% monitrily interest surcharge. Relinquished By: Date/Time: [11]7 Sample Condition: On Ice Sealed Intact Laboratory Use Only Temp. (F°) Yes / No Yes / No Received By: Results: Phone Email Fax RIN Time 6: 200 Initials N Date 1194 Contact () Date \ Time 7 nitials ---Prome Email Fax Phone Email Fax Contact Date Time Initials Date Time Initiate

1200 3232

Attachment I

Key to Count Sheets Count Sheets Analytical Procedures

Structures identifications consist of an Asbestos Type followed by a Structure Type

As bestos Type A = Amosite An = Anthophyllite C = Chrysotile Cr = Crocidolite T = Tremolite Structure Types F = Fiber B = Bundle C = Cluster M = Matrix

ND = no structures detected

M = other structure associated with a matrix

NAM = Non Asbestos Mineral


XGB = partly obscured by a grid bar

Sizing Conversion
1 length unit = 5 mm on screen = 0.278 micron
1.80 length units = 0.5 micron
18.0 length units = 5 microns

1 width unit = 1 mm on screen = 0.0556 micron

TEM Analysts

Jeanne S. Orr Nathan DelHierro Angela Heitger Jonathan Bemard Paul D. LoScalzo Mark Steiner Norberto Zimbleman Robert Workman



Upper and lower 95% confidence bounds for the number of structures counted assuming a Poisson distribution.

Reservoirs Environmental, Inc. TEM Asbestos Structure Count

Laboratory name:	REI
Instrument	JEOL 100 CX N 6
Voltage (KV)	100 KV
Magnification	(20KX) 10KX
Grkl opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0.056 um ·
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	N/A
QA Tyoe	NIA

R+R
A
1079
11/8/11
223858
820737

D OOD HUITIDGI.		
b Sample Number	820737	s
Factor Calculation (Indirect P	reps Only):	
action of primary filter used		
tal Resuspension Volume (ml)	;	
tume Applied to secondary fitter		

Analyzed by	- CR
Analysis date	11/8/11
Method (D=Dlrect, l=Indirect, IA=Indirect ashed)	D
Counting mles (ISO, AHERA, ASTM)	Att
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

Grid	GrM Opening	Structure	No. of St	ructures	Dimer	nsions	Identification	Mineral Class	Mineral Class			1 = yes, blank = no		
	Gilli Opolinig	Туре	Primary	Total	Length	Width	la Gridina de la	Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
A	95-4	M		·			PrepA	90/. War	4	~5]	debrs			
	75-4	NO		_			Prep B	NA						\
	25-4	NO						Jen 16	in	11/	8/11			
	CS-4	NO								-	/			•
B	F4-3	W												
	E4-3	W												
	C4-3	ND					·					`		
							,							

Reservoirs Environmental, Inc. TEM Asbestos Structure Count

Laboratory name:	REI
Instrument	JEOL 100 CX N &
Voltage (KV)	100 KV
Magnification	(20KX) 10KX
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0.056 um
Primaly filter area (mm2)	385
Secondaly Filter Area (mm2)	N/A
OA Type	NIA

Client :	R+R
Sample Type (A=Air, D=Dusi):	A
Alt volunte (L) or dust area (cm2)	1079
Date received by lab	11/8/11
Lab Job Number:	223858
Lab Sample Number:	820738
	

Analyzed by	-CR
Analysis date	11/8/11
Method (D=Direct, l=Indirect, IA=Indirect, ashed)	D
Counting rules (ISO, AHERA, ASTM)	AH
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzeti

F-Factor Calculation (Indirect Pro	eps Only):	
Fraction of primary filter used		
Total Resuspension Volume (ml)		
Volume Applied to secondary filter (ml)		

Grid	Grid Opening	Stmcture	No. of St	ructures	Dime	nsions	Identification	Mineral Class				1 = y	es, blank	= no
	Grid Operating	Туре	Primary	Total	Length	Width	Idominodion	Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
A	L4-3	ND				•	•			·	, , , , , , , , , , , , ,			
•	K4-3	M		·		me	p A 901	intact	~5	7, A	bris			
: .	H4-3	M				me	14		1					-
	194-3	M						Jon for	en 11/	8/11				
B	XU-1	W							<u> </u>					
	44-1	M												
	GH-1	M												
						·								
•							: :							. ,

Reservoirs Environmental, Inc. TEM Asbestos Structure Count

Laboratory name:	REI
Instrument	JEOL 100 CX N 6
Voltage (KV)	100 KV
Maonification	20KX 10KX
Grid opening area (mm2)	0.011
Scale: 1L=	0.28 um
Scale: 1D=	0.056 um
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	N/A
QA Tyoe	NJA

Client :	R+R
Sample Type (A=Air, D=Dust):	A
Air volume (L) or dust area (cm2)	1094
Date received by lab	11/8/11
Lab Job Number:	223858
Lab Sample Number:	820739

F-Factor Calculation (Indirect Preps Only):								
Fraction of primary filter used								
Total Resuspension Volume (m0		:						
Volume Applied to secondary litter (mt)								

Analyzed by	- CR
Analysis date	11/8/11
Method (D≠Direct, l⇒Indirect, 1A=Indirect, ashed)	D
Counting mles (ISO, AHERA, ASTM)	Att
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

Grid	Grid Opening	Structure	No. of St	ructures	Dimensions		Identification	Mineral Cless				1 = yes, blank = no		
		Туре	Primary	Total	Length	Width	Two real country	Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
A	93-1	M		<u>.</u>		•	Prox	A 90%.	15	1. de	bris			
	+3-1	120					frag C	> ~ A						
	23-1	10					·	Ven	Kno	~ 11/	8/11			
	(3-1	2												
B	K-3-1	M												
	H3-1	F		1	2.5	1	OD		-		- 62		·	
	93-1	NO												
														·
		}			,									
,								·						

Reservoirs Environmental, Inc. TEM Asbestos Structure Count

Client: P+R									
Cilent :	R+R								
Sample Type (A=Air, D=Oust):	A								
Air volume (L) or dust area (cm2)	1094								
Date received by leb	11/8/11								
Lab Job Number:	223858								
Lab Sample Number:	820740								

Analyzed by	-ac
Analysis date	11/8/11
Method (D=DirecL l=Indirect, IA=Indirect, ashed)	D
Counting miles (ISO, AHERA, ASTM)	AH
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

F-Factor Calculation (Indirect Preps Only):	F-Factor	Calculation	(Indirect	Preps	Only):
---	----------	-------------	-----------	--------------	--------

Fraction of primary filter used	
Total Resuspension Volume (mi)	
Volume Applied to secondary filter (ml)	

Grid	Grid Opening	Structure	No. of St	ructures	Dimer	nsions	identification	Hification Mineral Class				1 = yes, blank = no		
		Туре	Primary	Total	Length	Width		Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
A	96-4	M												L
	F6-4	M					Prep A	907. inta	45	-7/	debris			
	26-4	ND					Pner	Br4.		•	` .			
·	C10-4	M						Jen V	rer	11/8	/4			·
B	F4-6	M												
	24-6	M												
	64-6	W												
·														

REI

JEOL 100 CX N (S

100 KV

0.011

0.28 um

0.056 um

385

NA

NIA

Laboratory name:

Magnification Grid opening area

instrutnent

Vottage (KV)

Scale: 1L=

Scale: 1D =

Primary filter area

Secondary Fitter Area

(mm2)

(mm2)

(mm2)

QA Tyoe

Analytical Procedures - AHERA

Transmission electron microscopy/energy dispersive X-ray spectrometry/selected area electron diffraction (TEM/EDX/SAED) was employed in the analysis of the samples, which were collected on 25 mm mixed cellulose ester air filters. A portion of each filter was collapsed with acetone and etched in a plasma asher. The etched filter was then coated with a thin layer of carbon in a carbon side down. The sample was then placed inside a condensation washer and treated with acetone to remove the filter matrix and expose any inert material.

For each sample, enough grid openings on a 200 mesh TEM grid are analyzed to ensure an analytical sensitivity of at least 0.005 structures/cc. A minimum of four grid openings from two preparations are analyzed for each sample. The grid openings are searched for fibrous structures which, if present are analyzed by SAED and/or EDX (elemental analysis). The AHERA protocol requires SAED confirmation of enough chrysotile asbestos structures on each sample to cause the sample to exceed 70 structures/mm² (usually 4 or 5 structures). Both SAED and EDX confirmation are required of enough amphibole structures on each sample to cause the sample to exceed 70 structures/mm² (usually 4 or 5 structures) per sample. Either SAED or EDX is required for the remaining asbestos structures of either type. The morphology of each structure is determined and the length and the diameter of any asbestos structures are recorded. Asbestos fibers, bundles, cluster and matrices were identified and recorded. The asbestos structures have been defined in AHERA as follows:

Fiber: is a structure having a minimum length greater than or equal to 0.5

micron with an aspect ratio of 5:1 or greater with substantially parallel

sides.

Bundle: is a structure composed of three or more fibers in parallel arrangement,

with each fiber closer than the diameter of one fiber.

Cluster: is a structure with fibers in random arrangements such that all fibers are

intermixed and no single fiber is isolated from the group.

Matrix: is a fiber or fibers with one end free and the other end embedded or

hidden by a particulate. The exposed fiber end must meet the fiber

definition given above.

If more than 50 asbestos structures are identified and confirmed on a sample, AHERA analysis may be tenninated after completion of the grid opening, which contains the 50th structure. AHERA protocol requires the laboratory to reject any clearance sample which contains in excess of 25% total particulate loading or which appears to be unevenly loaded.

The AHERA protocol includes specific sampling requirements, including minimum numbers of samples and minimum air volumes. Specifically, the 70 structures/mm² clearance criteria is only allowed for sets five inside samples (collected in a group of 13 samples including: five outsides and three blanks) with volumes greater than 1200 liters (40 CFR Part 763, page 41894). Deviation from the AHERA sampling protocol may affect the validity of the analyfical results. Analysis of samples collected by non-protocol methods are not accredited by NVLAP

Equations Used for Calculations

Area Analyzed, $mm^2 = \# GO \text{ counted } x \text{ Average GO Area (mm)}$

Concentration, $s/cc = \frac{\text{\# Asbestos Structures}}{\text{\# GO Counted}} \times \frac{1}{\text{Volume (L)}} \times \frac{\text{Eff. Filter Area (mm}^2)}{\text{Average GO area (mm}^2)} \times \frac{1L}{1000cc}$

Filter loading, s/mm² = # Asbestos structures Area Analyzed (mm²)

GO = TEM grid opening